



**Installation**

Tightening torque (M5) : 20.4-30.9 in-lb (2.3 - 3.5 N-m)



**PULSEROLLER**  
 WEB: WWW.PULSEROLLER.COM  
 SUPPORT: SUPPORT@PULSEROLLER.COM  
 SALES: SALES@PULSEROLLER.COM

REV.	DATE	DESCRIPTION
A	21-MAY-2020	CONVERTED TO METRIC, UPDATE TITLE BLOCK
B	05-APR-2021	ADDED INSTALLATION TORQUE REQUIREMENTS

DATE: 21-MAR-2020	THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONJUNCTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.
DESIGNED BY: JPK	
CHECKED BY:	
SCALE: NONE	
SHEET: 1 OF 1	

TITLE: FIXING BRACKET - NON POWERED END PART NUMBER MR-DC-30P
FOR: SENERGY ACCESSORIES PULSEROLLER STANDARDS
DWG. NO: MR-DC-30P
REV: B