



Precautions
 Tightening torque (M6) : 70.8-88.5 (Lbf in)
 Tightening torque (M5) : 20.4-30.9 (Lbf in)

REV.	DATE	DESCRIPTION	THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONNECTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.
A	21-MAY-2020	CONVERTED TO METRIC, UPDATE TITLE BLOCK	DATE: 21-MAR-2015 DESIGNED BY: JPK CHECKED BY: SCALE: NONE
			TITLE: FIXING BRACKET - FLAT UP SHORT PART NUMBER PR-D-30H-FU-N-ST
			FOR: SENERGY ACCESSORIES PULSEROLLER STANDARDS
			DWG. NO: PR-D-30H-FU-N-ST
			REV: A

