



Precaution  
 Tightening torque(M6) : 8-10(Nm)  
 Tightening torque(M5) : 2.3-3.5(Nm)



|      |      |             |   |   |   |   |   |
|------|------|-------------|---|---|---|---|---|
| REV. | DATE | DESCRIPTION | ✓ | THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE AND IS PROPRIETARY INFORMATION OF INSIGHT AUTOMATION INC. AND SHALL BE USED ONLY IN CONJUNCTION WITH, AND PERFORMANCE OF, THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT INSIGHT AUTOMATION, INC. PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS. | DATE: 03/21/2014<br>DESIGNED BY:<br>CHECKED BY: | CUST.NO:<br>EST.NO:<br>ORD.NO:<br>SCALE: NONE<br>SHEET: 1 | TITLE: SENERGY SHORT BRACKET<br>FLAT UP FIXING BRACKET<br>FOR: CONTROL DRAWING<br>DWG. NO: PR-D-30H-FU-N-ST<br>REV: |
|------|------|-------------|---|---|---|---|---|