



Precautions
 Tightening torque (M6) : 70.8-88.5 (Lbf in)
 Tightening torque (M5) : 20.4-30.9 (Lbf in)

| | | | |
|---|-------------|---|--------|
| REV. | DATE | DESCRIPTION | ✓ |
| A | 21-MAY-2020 | CONVERTED TO METRIC, UPDATE TITLE BLOCK | |
| THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONJUNCTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS. | | | |
| DATE: 21-MAR-2015 | | TITLE: FIXING BRACKET - POINT UP SHORT | |
| DESIGNED BY: JPK | | PART NUMBER PR-D-30H-PU-N-ST | |
| CHECKED BY: | | FOR: SENERGY ACCESSORIES | |
| SCALE: NONE | | PULSEROLLER STANDARDS | |
| SHEET: 1 OF 1 | | DWG. NO: PR-D-30H-PU-N-ST | REV: A |

