



SENERGY-Ai

Optional spec.

Wash-down rated

- IP rating: IP-66
- Material: All stainless made (Pipe: SUS304, Side plate and shaft: SUS303)
- Roller diameter: 48.6, 50.0, 57.0, 60.5 (mm)
- Min. roller length: Refer to the "Available minimum roller length" table below.
- Max. roller length: 1000 mm *Contact us for longer than 1000 mm.
- Cable length: 1000 mm

Compatible Control Technologies



* Controls are not Wash-down rated.

Part numbers example

P R - W D - 50 - 500 - 45 A M A T

Spec.
W for Wash-down

Tube material & Rubber lagging option
A is standard for Wash-down rated.

Available minimum roller length

Roller diameter	Speed Code	Interlocking option			
		Plain straight	Micro V-Pulley	V-Pulley	Round Groove
48.6 / 50.0	15, 20, 25	360	344	351	381
	35, 45, 60, 75	332	317	324	354
	95, 125, 175, 215	309	294	301	330
57.0 / 60.5	15, 20, 25	347	N/A	341	347
	35, 45, 60, 75	320	N/A	314	320
	95, 125, 175, 215	296	N/A	290	296

Unit: mm

*We support even shorter length than those listed above using specially made components. Contact us for more details.

Optional spec.

Freezer rated

- Applicable Temp: From 0 down to -30°C (No condensation)
- Tube material: Mild steel, zinc plating / Stainless steel (SUS304)
- Side plate material: Aluminium
- Roller diameter: 48.6, 50.0, 57.0, 60.5 (mm)
- Min. roller length: Same as standard model
- Max. roller length: 1000 mm *Contact us for longer than 1000 mm.
- Cable length: 1000 mm

Compatible Control Technologies



* For freezer application, above controls need to be specially made. Please contact us for more details.

Part numbers example

P R - Z D - 50 - 500 - 45 Z M A T

Spec.
Z for Freezer rated