



Installation
 Tightening torque (M6) : 70.8-88.5 in-lb (8 - 10 N-m)
 Tightening torque (M5) : 20.4-30.9 in-lb (2.3 - 3.5 N-m)



PULSEROLLER
 WEB: WWW.PULSEROLLER.COM
 SUPPORT: SUPPORT@PULSEROLLER.COM
 SALES: SALES@PULSEROLLER.COM

REV.	DATE	DESCRIPTION
A	21-MAY-2020	CONVERTED TO METRIC, UPDATE TITLE BLOCK
B	05-APR-2021	CORRECTED DIMENSIONS

DATE:	21-MAR-2015
DESIGNED BY:	JPK
CHECKED BY:	
SCALE:	NONE
SHEET:	1 OF 1

TITLE:	FIXING BRACKET - FLAT UP SHORT
PART NUMBER	PR-D-30H-FU-N-ST
FOR:	SENERGY ACCESSORIES PULSEROLLER STANDARDS
DWG. NO.:	PR-D-30H-FU-N-ST
REV.:	B

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONNECTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.