



Installation

Tightening torque (M5) : 20.4-30.9 in-lb (2.3 - 3.5 N-m)



A	21-MAY-2020	CONVERTED TO METRIC. UPDATE TITLE BLOCK	THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONJUNCTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.	DATE: 21-MAR-2020	TITLE: FIXING BRACKET - NON POWERED END PART NUMBER MR-DC-30P FOR: SENERGY ACCESSORIES PULSEROLLER STANDARDS
B	05-APR-2021	ADDED INSTALLATION TORQUE REQUIREMENTS		DESIGNED BY: JPK	
C	10-APR-2024	UPDATED M5 FASTENERS		CHECKED BY:	
REV.	DATE	DESCRIPTION	✓	SCALE: NONE	DWG. NO: MR-DC-30P
				SHEET: 1 OF 1	REV: C