



Installation
 Tightening torque (M6) : 70.8-88.5 in-lb (8 - 10 N-m)
 Tightening torque (M5) : 20.4-30.9 in-lb (2.3 - 3.5 N-m)



PULSEROLLER
 WEB: WWW.PULSEROLLER.COM
 SUPPORT: SUPPORT@PULSEROLLER.COM
 SALES: SALES@PULSEROLLER.COM

A	21-MAY-2020	CONVERTED TO METRIC, UPDATE TITLE BLOCK	THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONJUNCTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.	DATE: 21-MAR-2015	TITLE: FIXING BRACKET - POINT UP SHORT
B	05-APR-2021	ADDED N-M VALUES FOR INSTALLATION TORQUE		DESIGNED BY: JPK	PART NUMBER PR-D-30H-PU-N-ST
REV.	DATE	DESCRIPTION	CHECKED BY:	SCALE: NONE	FOR: SENERGY ACCESSORIES PULSEROLLER STANDARDS
			SHEET: 1 OF 1	DWG. NO: PR-D-30H-PU-N-ST	REV: B