



Installation
Tightening torque (M5) : 20.4-30.9 in-lb (2.3 - 3.5 N-m)

A	21-MAY-2020	CONVERTED TO METRIC, UPDATE TITLE BLOCK	THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONNECTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.	DATE: 21-MAR-2020	TITLE: FIXING BRACKET - NON POWERED END
B	05-APR-2021	ADDED INSTALLATION TORQUE REQUIREMENTS		DESIGNED BY: JPK	PART NUMBER MR-DC-30P
				CHECKED BY:	FOR: SENERGY ACCESSORIES
				SCALE: NONE	PULSEROLLER STANDARDS
REV.	DATE	DESCRIPTION		SHEET: 1 OF 1	DWG. NO: MR-DC-30P
					REV: B

