



Unless otherwise specified upon order, Customer  
 Required Clearance is automatically set to 2 mm by  
 Pulseroller USA Order Entry System

INCLUDED ITEMS	
ITEM	DESCRIPTION
1	
2	PR-D-30H-XX-(XX) MOTOR SHAFT FIXING BRACKET - SPECIFY AT TIME OF ORDER

PR-AD-48-xxx-xxZSFQ	
TUBE DIA	48.6 mm
INTERLOCK	ROUND GROOVE PULLEY
MOTOR END	NON THREADED HEX SHAFT
IDLER END	SPRING LOADED HEX
CONNECTOR	JST - SENERGY

xxx = RL in mm  
 xx = Speed Code



**PULSEROLLER**  
 WEB: WWW.PULSEROLLER.COM  
 SUPPORT: SUPPORT@PULSEROLLER.COM  
 SALES: SALES@PULSEROLLER.COM

REV.	DATE	DESCRIPTION
A	20-MAY-2020	UPDATED DIMENSIONS TO METRIC
B	15-DEC-2020	ADDED CUSTOMER REQUIRED CLEARANCE
C	10-MAY-2021	CORRECTED LENGTH FORMULA
D	06-JUL-2021	ADDED DESCRIPTION CHART AND FIXING BRACKET

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL, IS SUBMITTED IN CONFIDENCE, AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONNECTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.

DATE: 21-MAR-2014  
 DESIGNED BY:  
 CHECKED BY:  
 SCALE: NONE  
 SHEET: 1 OF 1

TITLE: STANDARD 48 DIA ROUND GROOVE PULLEY  
 PART NUMBER PR-AD-48-xxx-xxZSFQ  
 FOR: SENERGY MOTOR ROLLER  
 PULSEROLLER STANDARDS  
 DWG. NO: PR-AD-48-xxx-xxZSFQ  
 REV: D