



Unless otherwise specified upon order, Customer
 Required Clearance is automatically set to 2 mm by
 Pulsroller USA Order Entry System

INCLUDED ITEMS		QTY
ITEM	DESCRIPTION	QTY
1		0
2	PR-D-30H-XX-(XX) MOTOR SHAFT FIXING BRACKET - SPECIFY AT TIME OF ORDER	1

PR-AD-48-xxx-xxZSGQ	
TUBE DIA	48.6 mm
INTERLOCK	DUAL GROOVE
MOTOR END	NON THREADED HEX SHAFT
IDLER END	SPRING LOADED HEX
CONNECTOR	JST - SENERGY

xxx = RL in mm
 xx = Speed Code



REV.	DATE	DESCRIPTION
A	20-MAY-2020	UPDATED DIMENSIONS TO METRIC
B	15-DEC-2020	ADDED CUSTOMER REQUIRED CLEARANCE
C	06-JUL-2021	ADDED DESCRIPTION CHART AND FIXING BRACKET

DATE	DESCRIPTION
21-MAR-2014	DESIGNED BY:
	CHECKED BY:
	SCALE:
	SHEET:

TITLE	FOR	DWG. NO.	REV.
STANDARD 48 DIA DUAL GROOVE	SENERGY MOTOR ROLLER	PR-AD-48-xxx-xxZSGQ	C
PART NUMBER PR-AD-48-xxx-xxZSGQ	PULSEROLLER STANDARDS		

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND IS SUBMITTED IN CONFIDENCE AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONNECTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.