



INCLUDED ITEMS		QTY
ITEM	DESCRIPTION	
1		0
2	PR-D-30H-XX-(XX) MOTOR SHAFT FIXING BRACKET - SPECIFY AT TIME OF ORDER	1

PR-AD-48-xxx-xxZSHQ	
TUBE DIA	48.6 mm
INTERLOCK	MICRO-V HUB
MOTOR END	NON THREADED HEX SHAFT
IDLER END	SPRING LOADED HEX
CONNECTOR	JST - SENERGY

Unless otherwise specified upon order, Customer Required Clearance is automatically set to 2 mm by Pulseroller USA Order Entry System

xxx = RL in mm
xx = Speed Code



REV.	DATE	DESCRIPTION
A	20-MAY-2020	UPDATED DIMENSIONS TO METRIC
B	15-DEC-2020	ADDED CUSTOMER REQUIRED CLEARANCE
C	06-JUL-2021	ADDED DESCRIPTION CHART AND FIXING BRACKET

REV.	DATE	DESCRIPTION
A	20-MAY-2020	UPDATED DIMENSIONS TO METRIC
B	15-DEC-2020	ADDED CUSTOMER REQUIRED CLEARANCE
C	06-JUL-2021	ADDED DESCRIPTION CHART AND FIXING BRACKET

DATE:	21-MAR-2014
DESIGNED BY:	
CHECKED BY:	
SCALE:	NONE
SHEET:	1 OF 1

TITLE:	STANDARD 48 DIA MICRO-V
PART NUMBER	PR-AD-48-xxx-xxZSHQ
FOR:	SENERGY MOTOR ROLLER PULSEROLLER STANDARDS
DWG. NO.:	PR-AD-48-xxx-xxZSHQ
REV.:	C

THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND IS PROPRIETARY INFORMATION OF PULSEROLLER AND SHALL BE USED ONLY IN CONNECTION WITH AND PERFORMANCE OF THE CONTRACT OF WHICH THIS DRAWING FORMS A PART, AND SHALL NOT, WITHOUT PULSEROLLER PRIOR WRITTEN APPROVAL, BE REPRODUCED OR IN ANY OTHER WAY USED IN WHOLE OR IN PART BY OTHERS.